

US009460865B2

(12) United States Patent

Worsley et al.

(54) MECHANICALLY ROBUST, ELECTRICALLY CONDUCTIVE ULTRALOW-DENSITY CARBON NANOTUBE-BASED AEROGELS

(71) Applicant: LAWRENCE LIVERMORE NATIONAL SECURITY, LLC,

Livermore, CA (US)

(72) Inventors: Marcus A. Worsley, Hayward, CA

(US); Theodore F. Baumann, Discovery Bay, CA (US); Joe H. Satcher, Jr., Patterson, CA (US)

(73) Assignee: Lawrence Livermore National

Security, LLC, Livermore, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 15/152,801

(22) Filed: May 12, 2016

(65) **Prior Publication Data**

US 2016/0260550 A1 Sep. 8, 2016

Related U.S. Application Data

- (60) Continuation of application No. 14/179,271, filed on Feb. 12, 2014, now Pat. No. 9,384,870, which is a division of application No. 12/652,616, filed on Jan. 5, 2010, now Pat. No. 8,685,287.
- (60) Provisional application No. 61/147,694, filed on Jan. 27, 2009.
- (51) Int. Cl. *H01B 1/06* (2006.01) *H01B 1/24* (2006.01)

(Continued)

(10) Patent No.: US 9,460,865 B2

(45) **Date of Patent:** *Oct. 4, 2016

11/38 (2013.01);

(Continued)

58) Field of Classification Search

USPC 252/500, 502, 510; 977/742, 752, 932 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

5,260,855 A 11/1993 Kaschmitter et al. 5,409,683 A 4/1995 Tillotson et al.

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO-2008/000163 A1 1/2008

OTHER PUBLICATIONS

Bordjiba, T. et al. (2008) "New Class of Carbon-Nanotube Aerogel Electrodes for Electrochemical Power Sources," Adv. Mater. 20:815-819.

(Continued)

Primary Examiner — Bijan Ahvazi (74) Attorney, Agent, or Firm — Foley & Lardner LLP

(57) ABSTRACT

Disclosed here is a device comprising a porous carbon aerogel or composite thereof as an energy storage material, catalyst support, sensor or adsorbent, wherein the porous carbon aerogel comprises a network of interconnected struts comprising carbon nanotube bundles covalently crosslinked by graphitic carbon nanoparticles, wherein the carbon nanotubes account for 5 to 95 wt. % of the aerogel and the graphitic carbon nanoparticles account for 5 to 95 wt. % of the aerogel, and wherein the aerogel has an electrical conductivity of at least 10 S/m and is capable of withstanding strains of more than 10% before fracture.

20 Claims, 10 Drawing Sheets

